



GROUND FORCE

HORTICULTURAL PRODUCTS



PERFORMANCE **GROWN** THROUGH TECHNOLOGY...

A specially formulated range of lubricants designed to keep both petrol and diesel horticultural equipment operating under severe operating conditions.

These include all-terrain vehicles (ATV), strimmers, lawnmowers, chainsaws and brush cutters.



Product Name	Pack Shot	Pack Sizes	Part No.	Applications	Specifications
Ground Force 10W-40 Horticultural Engine Oil		12 x 1L	GFS 001	Groundforce SAE 10W-40 is designed for use in all horticultural 4 stroke engines, both diesel and petrol where an oil of this quality is required.	API SF/CD/CF Approved and endorsed by BAGMA*
		4 x 5L	GFS 005		
		25L	GFS 025		
		205L	GFS 205		
Ground Force SAE 30 Horticultural Engine Oil		12 x 1L	SAE 001	For use in older diesel and petrol engines in horticultural equipment where an oil to API SF/CC quality is required.	API SF/CC Groundforce SAE 30 is approved and endorsed by BAGMA*
		4 x 5L	SAE 005		
		25L	SAE 025		
		205L	SAE 205		
Ground Force 2T Universal 2-Stroke Oil		12 x 1L	GTT 001	Groundforce 2T is designed for use in the engines of two stroke powered equipment in tool and horticultural hire shops. This includes chain saws, abrasive disc cutters, angle grinders, chippers, shredders, hover mowers, scarifiers, weed cutters, strimmers and hedge cutters.	API TC+, JASO FB Approved and endorsed by BAGMA*
		4 x 5L	GTT 005		
		25L	GTT 025		
		205L	GTT 205		
Ground Force 2HSS Universal 2 Stroke Oil		24 x 100ml	HSS 100	Formulated for use in the engines of all two stroke powered horticultural equipment. This includes mowers, chain saws, chippers, shredders, scarifiers, weed cutters, strimmers and hedge cutters. Can also be used in other air-cooled engines powering abrasive disc cutters, angle grinders and general 2-stroke hire equipment. Can also be used via a direct injection system.	API TC+, JASO FD ISO-L-EGD Approved and endorsed by BAGMA*
		12 x 1L	HSS 001		
		4 x 4L	HSS 004		
		25L	HSS 025		
Ground Force Croma 30 Chain & Cutter Bar Oil		12 x 1L	CRO 001	Groundforce Croma 30 is recommended for use in all chain lubrication systems and should be used in accordance to manufacturer's recommendations. Where biodegradable oils are required or desirable, Terralus CBO should be selected.	Approved and endorsed by BAGMA*
		4 x 5L	CRO 005		
		25L	CRO 025		
		205L	CRO 205		
Terralus CBO (Cutter Bar Oil)		4 x 5L	CVG 005	Terralus CBO is recommended for use in all chain lubrication systems and should be used accordingly to the manufacturers' recommendations.	Approved and endorsed by BAGMA*
		25L	CVG 025		
		205L	CVG 205		
Race ATV 10W-40 4-Stroke Engine Oil		12 x 1L	ATV 001	Race ATV 10W-40 is recommended for use in all-terrain vehicles, quad bikes, generator sets and other ancillary equipment, where a product of this type and viscosity grade is specified.	API SL JASO MA2
		4 x 4L	ATV 004		
		25L	ATV 025		
		205L	ATV 205		

* British Agricultural & Garden Machinery Association

Morris Lubricants sell a wide range of products to cover a multitude of applications. If you have a specific product requirement that is not covered in this brochure, please call a member of our sales team on 01743 232 200, or email info@morris-lubricants.co.uk.



ISO 9001
Quality
Management
Systems
CERTIFIED

FM 21756

ISO 14001
Environmental
Management
CERTIFIED

EMS 60044

ISO 45001
Occupational
Health and Safety
Management
CERTIFIED

OHS 555083

ISO 50001
Energy
Management
CERTIFIED

ENMS 619355



Verification of Lubricant Specifications
a subsidiary of BSI Ltd



UNITED KINGDOM LUBRICANTS ASSOCIATION



DRIVING STANDARDS
IN LUBRICANT TECHNOLOGY



MORRIS
LUBRICANTS

[/morrislubricants](https://www.facebook.com/morrislubricants) | [@morrislubricantsuk](https://www.instagram.com/morrislubricantsuk) | [/morris-lubricants](https://www.linkedin.com/company/morris-lubricants)

www.morrislubricants.co.uk

All the products are reflective of the latest specifications at the time of going to press and are part of a continuous development programme. The company reserves the right to change formulation and specification, without prior notice to meet the latest trends and developments in lubricant and grease technology. For more detailed information on any product and confirmation of the latest specifications contact our Technical Services Department. Full product data sheets and health and safety information is available on request.