



Product Information:

MULTIVIS ECO VA 0W-30 MULTIVIS ADT VA 5W-30 SYNTHETIC TECHNOLOGY – MID-SAPS

Description

Multivis ADT VA 5W-30 and Multivis ECO VA 5W-30 0W-30 are synthetic technology lubricants, designed for use in the latest engines, including those fitted with exhaust gas after-treatment devices.

These lubricants have the following benefits:

1. Increased engine efficiency.
2. Outstanding fuel economy.
3. Provides extended oil drain capability.
4. Rapid cold start flow that reduces noise and wear.
5. Increased film strength at high temperatures under all driving conditions.
6. High temperature deposit and anti-sludge control.
7. Low levels of volatility.

Applications

Multivis ADT VA 5W-30 and Multivis ECO VA 0W-30 are recommended for the latest petrol and diesel engines, including turbo-charged versions and those fitted with exhaust gas after-treatment devices such as particulate filters, catalytic converters, exhaust gas re-circulation, etc. May be used in all VAG vehicles employing fixed service or long life service maintenance schedules where the use of engine oils approved to VW 504.00 / 507.00 are specified and where VW 503.00/503.01/506.00/506.01 performance levels have previously been required.

Multivis ADT VA 5W-30 and 0W-30 may also be used in other manufacturer's engine types requiring a lubricant of these viscosity grades and performance levels.

Performance Levels

Approved under VW Standard 504 00 and VW Standard 507 00

ACEA C3

Porsche C30

MB 229.51

BMW Longlife-04

Physical Characteristics

Grade	ECO	ADT
SAE Classification	0W-30	5W-30
Viscosity @ 100°C, cSt.	11.9	11.3
Viscosity @ 40 °C, cSt.	61.6	63.4
Viscosity Index	194	174
Density @ 15.6°C	0.844	0.852
Flash Point (Closed) °C	196	194
TBN, mg/KOH/g	8.2	8.2
Pour Point, °C	-45	-42

Figures based on average production values.

Part No.s: VMX001, VMX005, VMX025, VMX205
EVA001, EVA005, EVA025, EVA205

(TDS Multivis ADT VA 5W-30 and 0W-30 – 040924 Issue1)

