



Product Information: **DUPLEX CDX 15W-40**

Description

Duplex CDX 15W-40 is a mixed fleet lubricant, incorporating high quality minerals oils and performance additives, suitable for use in a wide variety of diesel and petrol engine designs, including turbocharged versions. This grade will protect engine components from rust and corrosion and provide high levels of engine cleanliness, even in extended oil drain applications.

Applications

Duplex CDX 15W-40 can be used in a range of vehicle and engine types, including commercial vehicles, buses, coaches, cars and vans, plant, construction and agricultural machinery. Duplex CDX 15W-40 may also be used in transmissions, hydraulic systems, PTOs, compressors, etc. where a product of this type and specification is required.

Performance Levels

API CG-4 / CF / SL / SJ
Mercedes Benz 229.1
Mercedes Benz 228.1
MAN 271
Mack EO-L
Volvo VDS2
VW 505.00
Allison C4
BR 669 (Multigrade Crankcase Oil 15W-40)

Physical Characteristics

Appearance	Amber liquid
Density @ 15.6°C	0.880
Kinematic Viscosity @ 40°C (cSt)	102.1
Kinematic Viscosity @ 100°C (cSt)	14.3
Viscosity Index	145
CCS @ -20°C (mPas)	7000 max
Closed Flash point (°C)	205
Pour Point (°C)	-35
TBN (mgKOH/g)	9.8
Sulphated Ash (%Wt)	1.3

Figures based on average production values.

Part No.s: CDX025, CDX205

(TDS Duplex CDX 15W-40 – 160819 Issue 17)

