



Product Information:

MULTIVIS ECO FA 0W-30 **FUEL EFFICIENT MID-SAPS ENGINE OIL**

Description

Multivis ECO FA 0W-30 is a mid-SAPS engine oil formulated for use in Ford and JLR's latest technology diesel engines and where superior fuel efficiency performance is required. Can be used in engines specifying low viscosity lubricants, either in gasoline or diesel applications, where the performance levels quoted below are listed. Multivis ECO FA 0W-30 has been developed for use in Euro V and VI compliant vehicles with DPF after treatment devices.

Multivis ECO FA 0W-30 provides:

1. Increased engine efficiency, output and improved fuel economics.
2. Outstanding cold temperature flow rates and high temperature film strength.
3. Low levels of volatility.
4. Superior thermal stability, improved engine cleanliness.

Applications

Recommended for use in the latest Ford and Jaguar Land Rover engine designs, requiring a low viscosity grade complying with the specifications listed below:

Performance Levels

Ford WSS-M2C950-A
ACEA C2
STJLR.03.5007 (Verified)

Physical Characteristics

Viscosity @ 100°C, cSt.	9.52
Viscosity @ 40°C, cSt.	45.67
Viscosity Index	196
Density @ 15.6°C	0.840
Flash Point (Closed) °C	210
TBN, mg/KOH/g	8.0
Pour Point, °C	-48

Figures based on average production values.

Part No.s: NFT001, NFT005, NFT025, NFT205

(TDS Multivis ECO FA 0W-30 – 141019 Issue 3)

