



MORRIS
LUBRICANTS

Product Information:
MULTIVIS CST ME
10W-30 & 15W-40

Description

Multivis CST ME 10W-30 and 15W-40 are engine oils manufactured from high quality base oils and a high performance additive system. These grades have been optimised for use in petrol engines, naturally aspirated and turbocharged versions. Multivis CST ME 10W-30 is semi-synthetic.

Multivis CST ME 10W-30 and 15W-40 engine oils provide a high level of engine cleanliness and control the formation of high temperature lacquers and low temperature sludges. Powerful anti-wear technology ensures maximum component life, together with protection from oxidation, rust and corrosion.

Key Features

- Outstanding Soot Handling
- Enhanced Sludge Dispersancy
- High levels of Piston Cleanliness
- Improved Anti-wear protection

Applications

Multivis CST ME 10W-30 and 15W-40 are engine oils are suitable for use in passenger cars, light commercial vehicles, etc. where an oil of this type and specification is required.

Performance Levels

API SP

Physical Characteristics:

SAE Classification	10W-30	15W-40
Appearance	Amber liquid	Amber liquid
Density @ 15°C	0.870	0.875
Viscosity @ 40°C (cSt)	65.9	103.6
Viscosity @ 100°C (cSt)	9.9	13.5
Viscosity Index	130	130
CCS (mPas)	5700 @ -25°C	6300 @ -20°C
Closed Flash Point (°C)	210	220
Pour Point (°C)	-39	-30
Base Number (mg/KOH/g)	7.4	7.4

Figures based on average production values

(TDS Multivis CST ME 10W-30 / 15W-40 – 261124 Issue 3)

