



Product Information:

## LIQUIMATIC SUPER ATF AUTOMATIC TRANSMISSION OIL

### Description

Liquimatic Super ATF is an automatic transmission fluid blended from high quality mineral oil and a balanced additive system. This grade has superior performance in terms of frictional characteristics, seal compatibility, oxidation stability, low temperature fluidity and resistance to high temperatures encountered during severe operating conditions.

### Applications

Liquimatic Super ATF is recommended for use in a range of applications, where a product of this quality is specified. Applications include: automatic transmissions, powershift transmissions, transaxles, torque converters, hydrostatic drives, fluid couplings, fluid clutches, transfer boxes, brake boosters, levelling systems, hydraulic systems, bogie lifts, cab tilt mechanisms, motorcycle suspension forks, etc.

**DO NOT USE** in automotive transmissions specifying Ford ESW-M2C33-F fluids (see Liquimatic 33G).

### Performance Levels

Allison TES-228 (C-4)  
ATF LT71141 / 7045E / 3100 / 3403-M115 / N402  
BMW ATF4 / ETL-7045E / ETL-8072B / ETL-8072B / LA2634  
Chrysler ATF+ / +2 / +3 (MS 7176E)  
Ford Mercon® / ESP-M2C138-CJ / I66-H / I28-C / I28-D / 922-AI / XT-2-QDX/M  
GM Dexron® II / IID / IIE / IIIG / IIHH / TASA  
GM 1940700 / 21005966  
Hyundai – Kia Dex-II / SP-II  
Jaguar JLM 20238 / M115 / JLM 20292  
Jeep ATF+3  
MAN 339A / 339D / 339F  
Mazda ATF N-I / ATF S-2 / F-I  
Mercedes 236.1 / 236.10 / 236.11 / 236.2 / 236.5 / 236.8  
Mitsubishi DII/DIII  
Nissan Fluid A / Matic D / N402  
Opel/GM 19 40 700 / 19 40 767 / 21005966 Transaxle / 22 17266  
Porsche 000 043 205 09 / 999 917 547 00 (A2) /  
Peugeot-Citroen B71 2340 / AL4 Auto Gearbox Oil (#9730.AE)  
Renault SATF-D / Matic D2 / DP-0  
Suzuki ATF 2326 / 2384K / 5D06 / Matic D2  
Toyota Type D-II / Type T / Type T-II  
Volvo 97325 / 97335 / PN. 1161521 / PN. 1161621  
VW G-052 162 / G-052 990  
ZF TE-ML 05L / 21L / Lifeguard 5  
ZF all 3 and 4 speed

### Physical Characteristics

Appearance	Red
Density at 15.6 °C	0.858
Viscosity @ 100 °C, cSt.	7.1
Viscosity @ 40 °C, cSt.	35.9
Viscosity Index	167
Flash Point (Closed) °C	195
Pour Point, °C	-51

Figures based on average production values.

Part No.S: ATF001, ATF005, ATF025, ATF205

(TDS Liquimatic Super ATF – 050624 Issue 18)

