Product Information:

# MULTIVIS ECO VB 0W-20

## FUEL EFFICIENT ENGINE OIL

### Description

Multivis ECO VB 0W-20 is a high performance fully synthetic engine oil formulated to cope with the exacting demands of OEMs requiring low viscosity engine oils, in particular Volkswagen Audi Group. The product uses a combination of synthetic base fluids and an advanced additive system to provide a balanced lubricant that delivers friction reduction, component protection and fuel efficiency.

Multivis ECO VB 0W-20 provides the following benefits:

- Contributes to overall fuel efficiency
- Circulates rapidly from cold
- Strong oil film protects at high temperatures and under arduous work loads
- Ensures a high level of component cleanliness and operational efficiency

### Applications

Recommended for use in engines where a lubricant of this viscosity and performance level is specified in handbooks.

### Performance Levels

Approved under VW Standard 508 00 and VW Standard 509 00
ACEA C5, ACEA C6
API SQ, API SQ-RC
API SP, API SP-RC
ILSAC GF-7A, ILSAC GF-6A
VW TL 52577
Porsche C20
China GB11121
Ford WSS-M2C956-A1

### Physical Characteristics

| | | |
|---|---|---|
| Viscosity @ 100°C, cSt. | | 7.81 |
| Viscosity @ 40°C. cSt. | | 38.97 |
| Viscosity Index | 176 | |
| Density @ 15.5°C | | 0.837 |
| Flash Point (Closed) °C | | 210 |
| TBN, mg/KOH/g | 8.30 | |
| Pour Point °C | | -57 |

Figures based on average production values.