



Product Information:

Multivis ECO T 0W-8 FUEL EFFICIENT ENGINE OIL FOR HYBRIDS

Description

Multivis ECO T 0W-8 is a high performance synthetic engine oil formulated to cope with the exacting demands of hybrids, where fast circulation is required and when the engine can be immediately under load. Under stop/start conditions this lubricant will protect bearings and critical valve gear.

The continuing drive to reduce emissions and improve fuel efficiency, has produced advances in engine hardware design and this in turn has moved engine oil technology to the next level.

The 0W-8 classification was launched to further enhance an engine's ability to run more efficiently whilst using less fuel and therefore producing less CO₂.

Protects high output small petrol engines using gasoline direct injection and turbocharging. Also compatible with gasoline particulate filters.

Multivis ECO T 0W-8 provides the following benefits:

- Contribution to overall fuel efficiency
- Rapid circulation from cold
- Strong oil film that protects at high temperatures and under arduous work loads
- A high level of component cleanliness and operational efficiency
- Low volatility and minimal oil consumption
- Reduces emissions

Applications

Recommended for use in engines where a lubricant of this viscosity and performance level is specified in handbooks, including Toyota and Mazda.

Performance Levels

JASO GLV-1

ILSAC GF-5

API SN

Physical Characteristics

Viscosity @ 100°C, cSt.	5.3
Viscosity @ 40°C, cSt.	25.9
Viscosity Index	142
Density @ 15.5°C	0.845
Flash Point (Closed) °C	210
TBN, mg/KOH/g	7.0
Pour Point °C	-42

Figures based on average production values.

Part No.s: MET001, MET004, MET005

(TDS Multivis ECO T 0W-8 – 120324 issue 1)

