



Product Information:

VERSIMAX[®] HD15 5W-30 **ADVANCED FUEL EFFICIENT DIESEL ENGINE OIL**

Description

Versimax[®] HD15 5W-30 is a heavy duty diesel engine oil, manufactured from Group III base fluids. This product contains an advanced additive package formulated to provide the utmost protection when operating in very severe conditions with extended drain intervals.

Versimax[®] HD15 5W-30 has been developed for use in diesel engines fitted with exhaust gas re-circulation (EGR), selective catalytic reduction (SCR – Adblue) NO_x reduction systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF).

Versimax HD15 5W-30 maximises fuel efficiency potential by producing a thin strong oil film whilst under load, which in turn reduces energy losses and CO₂ output.

Applications

Versimax[®] HD15 5W-30 is designed for use in Euro 6 compliant diesel engines capable of using low viscosity fuel efficient lubricants and where any of the performance levels shown below are specified. Market sectors include: commercial vehicles, coaches and buses,

Performance Levels

API FA-4 /SN
JASO DH-2
Cummins CES 20087
Detroit Diesel DFS 93K223

Approvals:

Volvo VDS-5 (Approval 417-0004-24-029)
Renault RLD-5 (Approval 417-0004-24-029)
Mack EOS-5 (Approval 417-0004-24-029)
Daimler Truck Fluid Release I5C130

Physical Characteristics

Density @ 15.6 °C	0.857
Viscosity @ 100°C,cSt.	9.8
Viscosity @ 40°C, cSt.	59.8
Viscosity Index	149
Flash Point (closed) °C	210
TBN, mg/KOH/g	9.9
Pour Point, °C	-45

Figures based on average production values.

Part No.s: VMT025, VMT205,

(TDS Versimax[®] HD15 5W-30 – I20525 Issue 3)

